

## Advantages

- Automation **DZ4 Biturbo**
- Leaf maximum weight **800 Kg**
- Up to 60 cycles per hour
- Internal gear from metal alloy
- Nylon gear unit housing with fiber
- Thermal protection 150C°
- Voltage: 127/220 Vac
- Gate speed: **34m/min**
- Opening in **5 seconds** \*

\* Gate with 3 meters according to weight



## DZ4 SK BITURBO



A The Semi-Industrial Turbo line with its bold reduction system with differentiated gear, resistant and insulating reducer body, makes the product reliable and with a great performance.

**Models: DZ4 SK TURBO 127V - DZ4 SK TURBO 220V**

### Benefits:

- . Built-in BIKXH1024-FS electronic control board with anti-cloning system.
- . Internal alloy crown
- . Clutch adjustment for anti-smash
- . Fairing with ultraviolet protection
- . Driver base with insulation material
- . Available in 127V/220V

| FEATURES                 | DZ4 BITURBO                   |
|--------------------------|-------------------------------|
| Maximum Gate Weight (kg) | 800                           |
| Speed (m/min)            | 34                            |
| Aplication               | Semi-Industrial / condominial |
| Power Supply (Vac)       | 127 / 220                     |
| Speed sec/m:             | 1,7                           |
| Cicles/h                 | 40                            |
| Maximum Power (W)        | 500                           |
| Rack module              | 4                             |
| Termic protection (°C)   | 150                           |
| Frequency (Hz)           | 50/60                         |
| Protection IP            | 44                            |
| Consumption (A)          | 3 / 1,7                       |
| Maximum Rotation (rpm)   | 3240                          |
| Unlocking                | Key                           |

### Accessories:

- . Transmitter
- . Photocell
- . Receptor
- . Accessory devices
- . Racks
- . Flashing lamps

